



### Long Service Life

Advanced wear-resistant compound with dual-layer tread offers long service life.

### Wide Footprint

Premium 5-rib design with wide footprint offers slow, uniform wear and enhanced handling.

### All-Weather Traction

Special groove design and rib edge sipes enhances traction in all weather conditions.

### Guaranteed Retreadability

Premium casing construction promotes consistent footprint and guaranteed retreadability.

SIZE	PR / LR	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER [MM / IN.]	SECTION WIDTH [MM / IN.]	SINGLE LOAD [KG/LBS]	DUAL LOAD [KG/LBS]	PRESSURE [KPA / PSI]	TREAD DEPTH [MM / 32NDS]	PRODUCT CODE
11R22.5	14 / G	144/142 L	8.25	1065 / 41.9	279 / 11.0	2800/6175	2650/5840	720 / 105	14.3 / 18.0	6959613724237
11R22.5	16 / H	148/145 L	8.25	1054 / 41.5	279 / 11.0	3150/6940	2900/6390	850 / 123	14.3 / 18.0	6959613724244
295/75R22.5	14 / G	144/141 M	9.00	1014 / 39.9	298 / 11.7	2800/6175	2575/5675	760 / 110	14.3 / 18.0	6959613724299
295/75R22.5	16 / H	146/143 M	9.00	1014 / 39.9	298 / 11.7	3000/6610	2725/6005	830 / 120	14.3 / 18.0	6959613724305
315/80R22.5	20 / L	157/154 L	9.00	1076 / 42.4	312 / 12.3	4125/9090	3750/8270	900 / 130	15.9 / 20.0	6959613724312
11R24.5	14 / G	146/143 L	8.25	1116 / 43.9	279 / 11.0	3000/6610	2725/6005	720 / 105	14.3 / 18.0	6959613724251
11R24.5	16 / H	149/146 L	8.25	1104 / 43.5	279 / 11.0	3250/7160	3000/6610	830 / 120	14.3 / 18.0	6959613724268
285/75R24.5	14 / G	144/141 L	8.25	1050 / 41.3	283 / 11.1	2800/6175	2575/5675	760 / 110	14.3 / 18.0	6959613724275
285/75R24.5	16 / H	147/144 L	8.25	1050 / 41.3	283 / 11.1	3075/6780	2800/6175	830 / 120	14.3 / 18.0	6959613724282