





#### Drive the New World!

Keter (pronounced like Better), is the Hebrew word for "Crown", it can also mean "Top" or "Crest". The Keter Corporation was founded in 2009 with the vision, and mission, to be widely recognized as one of the Top Tire Suppliers in Tire Industry.

Over the past decade, Keter's Customer Centric Philosophy has earned the reputation of a different kind of Tire Supplier. One that is very accommodating and easy to do business with. We are a Global Product Sourcing Enterprise with a very simple business model that allows us to address the unique needs of our individual Customers. Our Customers see us not only as a strategic source for tires, and related products, but also as a trusted partner who is committed as much to their success, as to our own.

Keter Tire USA offers an extensive product line up in passenger, light truck and commercial truck products including the NeoTerra line which was specifically designed and developed to meet the demands of the US market.

#### NeoTerra

The NeoTerra brand offers some of the most Technologically Advanced products available. Focused on a balance between Performance, Durability and Safety, and delivered at a value price point.

All NeoTerra products are produced using the latest equipment and the most advanced facilities in the industry.

- Advanced technology
- Proven quality, performance and durability
- Environmentally responsible
- Outstand warranty and satisfaction guarantee

Wherever the road takes you, it's our mission to help advance your journey. We will be there with you as you drive your new worlds.

Drive Well and Safe Travels.

**Rick Phillips**, CEO

# NEOTERRA



NeoTerra Brand products are produced utilizing the world's most advanced manufacturing technology, with three fundamental principles:

- technology to improve driver safety.
- performance.
- and driving situation.



**Every NeoTerra Product Comes With a** MONEY BACK GUARANTEE.

• Safety is in everything we do and we leverage the most advanced process and

Relentless pursuit of quality and rigorous process control to deliver reliable product

• Our products are engineered with great durability to stand up to every application

## PASSENGER



#### **NEOTERRA COMMERCIAL TRUCK TIRES**

4-belt casing construction for guaranteed readability and durable performance.

- Dual-compound tread with specially formulated compounds allow for longer wear and lower rolling resistance.
- Wide body construction for an expanded footprint on the road to improve stability and lateral handling.
- Developed and Manufactured utilizing the most advanced technologies in the tire industry.

## **NEOTERRA® COMMERCIAL TRUCK TIRE STANDARD WARRANTY**

More than giving drivers added peace of mind, NeoTerra Commercial Truck Standard Warranty shows our commitment to provide tires with high quality, dependability and reliability.

#### **30-DAY SATISFACTION ASSURANCE**

Congratulations on driving your new NeoTerra truck tires! Our confidence, your comfortability. Within 30 days of purchase, if you or your driver are not completely satisfied with NeoTerra commercial truck tires, simply bring them back to the authorized dealer where you made the purchase for a full refund or exchange for a different set of tires. And, we will cover the cost of replacement tires installation!

#### 60-DAY ROAD HAZARD PROTECTION

Rest easy from hard-to-avoid road hazards, you are covered under NeoTerra limited Road Hazard Warranty. Every NeoTerra commercial truck tire designed and operated in an over-the-road application is covered for damage caused by normal road hazard condition within the first 4/32nd of tread life or 60 days from date of purchase, whichever comes first. Un-repairable tire will be replaced free of charge with a NEW NeoTerra tire. Exclusions and conditions are listed under NeoTerra Standard Warranty.

#### LIFETIME REPLACEMENT WARRANTY

For your peace of mind, Keter Tire USA warrants NeoTerra commercial truck tire products for defects in workmanship and materials for the lifetime of the original tread down to 2/32nd of measurable tread. The lifetime of the original tread is defined tread that has worn down to 2/32nd measured in the fastest wearing groove. Keter Tire USA will replace the tire with another comparable NeoTerra tire for no charge during first 25% of original tread life and pro-rated replacement down to 2/32nd of remaining usable tread. Exclusions and owner's obligations are listed under NeoTerra Standard Warranty.

#### **CASING WARRANTY**

Keter Tire USA warrants NeoTerra commercial truck tire for workmanship and materials at 100% through the first and second retread for a period of five (5) or six (6) years, depending on product, from date of purchase or date manufacturer without proof of purchase.



## AP201 | REGIONAL ALL POSITION

## Long Service Life

Advanced wear-resistant compound with dual-layer tread offers long service life. 00 0

### **Wide Footprint**

Premium 5-rib design with wide footprint offers slow, uniform wear and enhanced handling.

#### **All-Weather Traction**

Special groove design and rib edge sipes enhances traction in all weather conditions.

## **Guaranteed Retreadability**

Premium casing construction promotes consistent footprint and guaranteed retreadability.

|    | SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STANDARD<br>RIM | OVERALL<br>DIAMETER<br>[MM / IN] | SECTION<br>WIDTH<br>[MM / IN ] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL<br>LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|----|-------------|---------|------------------------------|-----------------|----------------------------------|--------------------------------|----------------------------|--------------------------|-------------------------|------------------------------|-----------------|
| 11 | 11R22.5     | 14 / G  | 144/142 L                    | 8.25            | 1065 / 41.9                      | 279 / 11.0                     | 2800/6175                  | 2650/5840                | 720 / 105               | 14.3 / 18.0                  | 6959613724237   |
|    | 11R22.5     | 16 / H  | 148/145 L                    | 8.25            | 1054 / 41.5                      | 279 / 11.0                     | 3150/6940                  | 2900/6390                | 850 / 123               | 14.3 / 18.0                  | 6959613724244   |
|    | 295/75R22.5 | 14 / G  | 144/141 M                    | 9.00            | 1014 / 39.9                      | 298 / 11.7                     | 2800/6175                  | 2575/5675                | 760 / 110               | 14.3 / 18.0                  | 6959613724299   |
|    | 295/75R22.5 | 16 / H  | 146/143 M                    | 9.00            | 1014 / 39.9                      | 298 / 11.7                     | 3000/6610                  | 2725/6005                | 830 / 120               | 14.3 / 18.0                  | 6959613724305   |
|    | 315/80R22.5 | 20 / L  | 157/154 L                    | 9.00            | 1076 / 42.4                      | 312 / 12.3                     | 4125/9090                  | 3750/8270                | 900 / 130               | 15.9 / 20.0                  | 6959613724312   |
|    | 11R24.5     | 14 / G  | 146/143 L                    | 8.25            | 1116 / 43.9                      | 279 / 11.0                     | 3000/6610                  | 2725/6005                | 720 / 105               | 14.3 / 18.0                  | 6959613724251   |
|    | 11R24.5     | 16 / H  | 149/146 L                    | 8.25            | 1104 / 43.5                      | 279 / 11.0                     | 3250/7160                  | 3000/6610                | 830 / 120               | 14.3 / 18.0                  | 6959613724268   |
|    | 285/75R24.5 | 14 / G  | 144/141 L                    | 8.25            | 1050 / 41.3                      | 283 / 11.1                     | 2800/6175                  | 2575/5675                | 760 / 110               | 14.3 / 18.0                  | 6959613724275   |
|    | 285/75R24.5 | 16 / H  | 147/144 L                    | 8.25            | 1050 / 41.3                      | 283 / 11.1                     | 3075/6780                  | 2800/6175                | 830 / 120               | 14.3 / 18.0                  | 6959613724282   |

# AP221 | SPECIALTY ALL POSITION

### Long Miles to Removal

\_\_\_\_\_\_

0

Innovative tread compound provides enhanced scrub resistance for long mileage to removal.

## **Superb Traction**

Geometric tread block design with special sipes offer superb traction and quick response on wet surfaces.

### **Enhanced Protection**

Wide enhanced shoulder provides increased protection against curb damage and irregular wear.

## **Guaranteed Retreadability**

Premium casing construction provides toughness and durability for guaranteed retreadability.

|    | SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL |      | OVERALL<br>DIAMETER<br>[MM/IN] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL<br>LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM / 32NDS] | PRODUCT<br>CODE |
|----|-------------|---------|------------------------------|------|--------------------------------|-------------------------------|----------------------------|--------------------------|-------------------------|--------------------------------|-----------------|
|    | 215/75R17.5 | 16 / H  | 127/124 M                    | 6.00 | 767 / 30.2                     | 211 / 8.3                     | 1750/3860                  | 1600/3525                | 830 / 120               | 12.8 / 16.1                    | 6959613724329   |
| N. | 235/75R17.5 | 18 / J  | 143/141 J                    | 6.75 | 797 / 31.4                     | 233 / 9.2                     | 2725/6010                  | 2575/5675                | 850 / 125               | 12.8 / 16.1                    | 6959613724343   |
|    | 225/70R19.5 | 14 / G  | 128/126 L                    | 6.75 | 811 / 31.9                     | 226 / 8.9                     | 1800/3970                  | 1700/3750                | 760 / 110               | 14.3 / 18.0                    | 6959613724336   |
|    | 245/70R19.5 | 16 / H  | 135/133 M                    | 7.50 | 839 / 33.0                     | 248 / 9.8                     | 2180/4805                  | 2060/4540                | 830 / 120               | 15.0 / 18.9                    | 6959613724350   |
|    | 255/70R22.5 | 16 / H  | 140/137 M                    | 7.50 | 930 / 36.6                     | 255 / 10.0                    | 2500/5510                  | 2300/5070                | 830 / 120               | 15.0 / 18.9                    | 6959613724367   |
|    | 275/70R22.5 | 16 / H  | 148/145 M                    | 8.25 | 958 / 37.7                     | 276 / 10.9                    | 3150/6940                  | 2900/6390                | 900 / 130               | 13.5 / 17.0                    | 6959613724374   |

# CD301 | CLOSED SHOULDER DRIVE

## Long Original Mileage

Deep tread with innovative compound promotes long original mileage.

00 00

4. 100

## **Uniform Wear**

Closed shoulder design provides uniform wear throughout the life of the tire

## **Enhanced Handling**


Aggressive design with wide footprint delivers enhanced handling and brake response.

## **Guaranteed Retreadability**

Premium casing construction provides toughness and durability for guaranteed retreadability.

|              | SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STAN-<br>DARD<br>RIM | OVERALL<br>DIAMETER<br>[MM / IN] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|--------------|-------------|---------|------------------------------|----------------------|----------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| III REMIE VA | 11R22.5     | 14 / G  | 144/142 L                    | 8.25                 | 1065 / 41.9                      | 279 / 11.0                    | 2800/6175                  | 2650/5840             | 720 / 105               | 21.4 / 27.0                  | 6959613724084   |
|              | 11R22.5     | 16 / H  | 146/143 L                    | 8.25                 | 1065 / 41.9                      | 279 / 11.0                    | 3000/6610                  | 2725/6005             | 830 / 120               | 21.4 / 27.0                  | 6959613724091   |
|              | 295/75R22.5 | 14 / G  | 144/141 L                    | 9.00                 | 1020 / 40.2                      | 298 / 11.7                    | 2800/6175                  | 2575/5675             | 760 / 110               | 21.4 / 27.0                  | 6959613724152   |
|              | 295/75R22.5 | 16 / H  | 146/143 L                    | 9.00                 | 1020 / 40.2                      | 298 / 11.7                    | 3000/6610                  | 2725/6005             | 830 / 120               | 21.4 / 27.0                  | 6959613724145   |
|              | 11R24.5     | 14 / G  | 146/143 L                    | 8.25                 | 1116 / 43.9                      | 279 / 11.0                    | 3000/6610                  | 2725/6005             | 720 / 105               | 21.4 / 27.0                  | 6959613724107   |
|              | 11R24.5     | 16 / H  | 149/146 L                    | 8.25                 | 1116 / 43.9                      | 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 21.4 / 27.0                  | 6959613724114   |
|              | 285/75R24.5 | 14 / G  | 144/141 L                    | 8.25                 | 1056 / 41.6                      | 283 / 11.1                    | 2800/6175                  | 2575/5675             | 760 / 110               | 22.5 / 28.3                  | 6959613724121   |
|              | 285/75R24.5 | 16 / H  | 147/144 L                    | 8.25                 | 1050 / 41.3                      | 283 / 11.1                    | 3075/6780                  | 2800/6175             | 830 / 120               | 22.5 / 28.3                  | 6959613724138   |

FIELD.



|  | SIZE        | PR / LR |
|--|-------------|---------|
|  | 225/70R19.5 | 14 / G  |
|  | 245/70R19.5 | 16 / H  |
| Long Service Life  | 10R22.5     | 14 / G  |
| Innovative tread compound and<br>advanced tread design deliver wear<br>resistance for a long service life. | 11R22.5     | 14 / G  |
| Superior Traction  | 11R22.5     | 16 / H  |
| Open shoulder design delivers<br>enhanced traction and acceleration in<br>all weather conditions.          | 255/70R22.5 | 16 / H  |
| Enhanced Handling  | 295/75R22.5 | 14 / G  |
| Aggressive design with wide footprint<br>delivers enhanced handling and<br>superior brake response.        | 295/75R22.5 | 16 / H  |
| Guaranteed Retreadability  | 11R24.5     | 14 / G  |
| Premium casing construction provides   |             |         |

00 0

Premium casing construction provides toughness and durability for guaranteed retreadability.

LOAD INDEX / STANDARD SPEED SYMBOL RIM

6.75

7.50

7.50

8.25

8.25

7.50

9.00

9.00

8.25

128/126 M

135/133 M

141/139 M

144/142 L

146/143 L

140/137 L

144/141 L

146/143 L

146/143 L

OVERALL DIAMETER [MM / IN ]

811 / 31.9

839 / 33.0

1020 / 40.2

1065 / 41.9

1065 / 41.9

930 / 36.6

1020 / 40.2

1020 / 40.2

1116 / 43.9

1116 / 43.9

|                               |                            |                       | 1000                    | 10 TO 10                     |                 |
|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
| 226 / 8.9                     | 1800/3970                  | 1700/3750             | 760 / 110               | 15.0 / 19.0                  | 6959613702686   |
| 248 / 9.8                     | 2180/4805                  | 2060/4540             | 830 / 120               | 15.0 / 19.0                  | 6959613702693   |
| 254 / 10.0                    | 2575/5675                  | 2430/5355             | 790 / 115               | 18.3 / 23.0                  | 6959613724169   |
| 279 / 11.0                    | 2800/6175                  | 2650/5840             | 720 / 105               | 20.6 / 26.0                  | 6959613724176   |
| 279 / 11.0                    | 3000/6610                  | 2725/6005             | 830 / 120               | 20.6 / 26.0                  | 6959613724183   |
| 255 / 10.0                    | 2500/5510                  | 2300/5070             | 830 / 120               | 17.5 / 22.0                  | 6959613724213   |
| 298 / 11.7                    | 2800/6175                  | 2575/5675             | 760 / 110               | 20.6 / 26.0                  | 6959613724220   |
| 298 / 11.7                    | 3000/6610                  | 2725/6005             | 830 / 120               | 20.6 / 26.0                  | 6959613729201   |
| 279 / 11.0                    | 3000/6610                  | 2725/6005             | 720 / 105               | 20.6 / 26.0                  | 6959613724190   |
| 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 20.6 / 26.0                  | 6959613724206   |
| 283 / 11.1                    | 2800/6175                  | 2575/5675             | 760 / 110               | 22.5 / 28.3                  | 6959613729225   |
| 283 / 11.1                    | 3075/6780                  | 2800/6175             | 830 / 120               | 22.5 / 28.3                  | 6959613729232   |

## **Ultimate Traction**

Functional tread design combined with a premium compound promotes ultra traction for all applications and harsh weather conditions.

#### **Powerful Grip**

Unique 3D sipes and optimized block design add extra gripping power in diverse weather conditions.

### **Added Traction Performance**

Unique groove and open shoulder design increases cleaning ability for added traction performance.

#### **Guaranteed Retreadability**

Premium casing construction provides toughness and durability for guaranteed retreadability.

| SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STANDARD<br>RIM | OVERALL<br>DIAMETER<br>[MM / IN] | SECTION<br>WIDTH<br>[MM / IN ] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|-------------|---------|------------------------------|-----------------|----------------------------------|--------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 11R22.5     | 14 / G  | 144/142 L                    | 8.25            | 1065 / 41.9                      | 279 / 11.0                     | 2800/6175                  | 2650/5840             | 720 / 105               | 22.5 / 28.3                  | 6959613701863   |
| 11R22.5     | 16 / H  | 146/143 L                    | 8.25            | 1065 / 41.9                      | 279 / 11.0                     | 3000/6610                  | 2725/6005             | 830 / 120               | 22.5 / 28.3                  | 6959613724459   |
| 295/75R22.5 | 14 / G  | 144/141 L                    | 9.00            | 1020 / 40.2                      | 298 / 11.7                     | 2800/6175                  | 2575/5675             | 760 / 110               | 22.5 / 28.3                  | 6959613701887   |
| 295/75R22.5 | 16 / H  | 146/143 L                    | 9.00            | 1020 / 40.2                      | 298 / 11.7                     | 3000/6610                  | 2725/6005             | 830 / 120               | 22.5 / 28.3                  | 6959613724473   |
| 11R24.5     | 14 / G  | 146/143 L                    | 8.25            | 1116 / 43.9                      | 279 / 11.0                     | 3000/6610                  | 2725/6005             | 720 / 105               | 22.5 / 28.3                  | 6959613701870   |
| 11R24.5     | 16 / H  | 149/146 L                    | 8.25            | 1116 / 43.9                      | 279 / 11.0                     | 3250/7160                  | 3000/6610             | 830 / 120               | 22.5 / 28.3                  | 6959613724466   |



#### COMMERCIAL TRUCK

## **Weight Savings**

**CT421** 

Wider, low profile design with advanced tread compound promotes weight savings and low rolling resistance.

## **Even Wear**

Optimized tread design provides even wear and long miles to removal.

## **Enhanced Strength**

Unique construction promotes durability and consistent footprint for enhanced strength and uniformity.

## **Guaranteed Retreadability**

Premium enhanced casing provides toughness and durability for guaranteed retreadability.

| SECTION<br>WIDTH<br>[MM / IN ] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|--------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 445 / 17.5                     | 4625/10200                 | /                     | 830 120                 | 14.3 / 18.0                  | 6959613726910   |

# CT401 | COMMERCIAL TRAILER

00 00

### Low Rolling Resistance

AL AL AL

Special tread compound with shallow non-skid offers low rolling resistance.

13

## **Enhanced Toughness and Even Wear**

Solid shoulder rib with unique pressure distribution grooves delivers enhanced toughness and promotes long, even wear.

## Wet Weather Stability

Wide center groove delivers superior water evacuation for increased stability in wet road conditions.

## **Guaranteed Retreadability**

Premium casing construction promotes multiple retreads.

| SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | Standard<br>Rim | OVERALL<br>DIAMETER<br>[MM/IN] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|-------------|---------|------------------------------|-----------------|--------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 11R22.5     | 14 / G  | 144/142 M                    | 8.25            | 1054 / 41.5                    | 279 / 11.0                    | 2800/6175                  | 2650/5840             | 720 / 105               | 10.7 / 13.5                  | 6959613724381   |
| 11R22.5     | 16 / H  | 146/143 M                    | 8.25            | 1054 / 41.5                    | 279 / 11.0                    | 3000/6610                  | 2725/6010             | 830 / 120               | 10.7 / 13.5                  | 6959613724398   |
| 295/75R22.5 | 14 / G  | 144/141 M                    | 9.00            | 1014 / 39.9                    | 298 / 11.7                    | 2800/6175                  | 2575/5675             | 760 / 110               | 10.7 / 13.5                  | 6959613724435   |
| 295/75R22.5 | 16 / H  | 146/143 M                    | 9.00            | 1014 / 39.9                    | 298 / 11.7                    | 3000/6610                  | 2725/6005             | 830 / 120               | 10.7 / 13.5                  | 6959613724442   |
| 11R24.5     | 14 / G  | 146/143 L                    | 8.25            | 1116 / 43.9                    | 279 / 11.0                    | 3000/6610                  | 2725/6010             | 720 / 105               | 10.7 / 13.5                  | 6959613724404   |
| 11R24.5     | 16 / H  | 149/146 L                    | 8.25            | 1116 / 43.9                    | 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 10.7 / 13.5                  | 6959613724411   |



00

## Long Service Life

201 2 2 4

Premium chip/cut resistant compound offers long service life in on and off road applications.

### **Improved Stability**

Optimized tread design with wider footprint improves stability and traction on various driving surfaces.

### **Adaptable Flexibility**

Special bead bundle package allows additional flexibility to manage unexpected road obstacles.

#### **Guaranteed Retreadability**

Premium enhanced casing construction offers toughness and outstanding performance through each retread cycle.

| SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STANDARD<br>RIM | OVERALL<br>DIAMETER<br>[MM / IN] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|-------------|---------|------------------------------|-----------------|----------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 11R22.5     | 16 / H  | 148/145 L                    | 8.25            | 1065 / 41.9                      | 279 / 11.0                    | 3150/6940                  | 2900/6390             | 850 / 123               | 18.3 / 23.0                  | 6959613724480   |
| 12R22.5     | 18 / J  | 152/149 K                    | 9.00            | 1085 / 42.7                      | 300 / 11.8                    | 3550/7830                  | 3250/7165             | 830 / 120               | 18.3 / 23.0                  | 6959613724510   |
| 255/70R22.5 | 16 / H  | 140/137 L                    | 7.50            | 930 / 36.6                       | 255 / 10.0                    | 2500/5510                  | 2300/5070             | 830 / 120               | 15.9 / 20.0                  | 6959613702730   |
| 275/70R22.5 | 16 / H  | 148/145 M                    | 8.25            | 958 / 37.7                       | 276 / 10.9                    | 3150/6940                  | 2900/6390             | 900 / 130               | 17.5 / 22.0                  | 6959613702747   |
| 315/80R22.5 | 20 / L  | 161/154 K                    | 9.00            | 1076 / 42.4                      | 312 / 12.3                    | 4625/10200                 | 3750/8270             | 900 / 130               | 18.3 / 23.0                  | 6959613724503   |
| 11R24.5     | 16 / H  | 149/146 L                    | 8.25            | 1104 / 43.5                      | 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 18.3 / 23.0                  | 6959613724497   |



| 2 | SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STANDARD<br>RIM | OVERALL<br>DIAMETER<br>[MM / IN ] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|---|-------------|---------|------------------------------|-----------------|-----------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
|   | 385/65R22.5 | 20/L    | 160 L                        | 11.75           | 1072 42.2                         | 389 / 15.3                    | 4500/9920                  | /                     | 900 130                 | 18.3 / 23.0                  | 6959613724527   |
|   | 425/65R22.5 | 20/L    | 165 K                        | 12.25           | 1124 44.3                         | 422 / 16.6                    | 5150/11400                 | /                     | 830 120                 | 18.3 / 23.0                  | 6959613724534   |
|   | 445/65R22.5 | 20 / L  | 168 K                        | 13.00           | 1150 45.3                         | 444 / 17.5                    | 5600/12350                 | /                     | 830 120                 | 18.3 / 23.0                  | 6959613724541   |



### **Enhanced Mileage**

Advanced severe service compound resists cut, chips and tears and offers a longer service life.

## **All-Season Traction**

Deep convex groove with biting edges provides all-season traction on wet, snowy or dry roads.

## **Improved Handling**

Optimized block pattern promotes excellent strength and improved handling.

#### **Guaranteed Retreadability**

Premium enhanced casing construction offers toughness and outstanding performance through each retread cycle.

#### **Extended Service Life**

00

Dependable cut/chip resistance compound promotes extended service life.

#### **Excellent Traction**

Rugged lug design provides deep non skid traction in severe off-highway service.

### **Guaranteed Retreadability**

Premium enhanced casing construction with deep undertread provides excellent retreadability.

| E | X  | X  |   |
|---|----|----|---|
|   | X  | XE |   |
| K |    |    |   |
|   | X  | XG |   |
| P | X  | X  |   |
| A | ST |    |   |
|   |    |    | o |
|   | X  | X  |   |

CONT STATE

| SIZE        | PR / LR | LOAD INDEX /<br>SPEED SYMBOL | STANDARD<br>RIM | OVERALL<br>DIAMETER<br>[MM/IN] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|-------------|---------|------------------------------|-----------------|--------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 11R22.5     | 16 / H  | 146/143 L                    | 8.25            | 1065 / 41.9                    | 279 / 11.0                    | 3000/6610                  | 2725/6005             | 830 / 120               | 23.8 / 30.0                  | 6959613724558   |
| 315/80R22.5 | 20 / L  | 161/154 K                    | 9.00            | 1076 / 42.4                    | 312 / 12.3                    | 4625/10200                 | 3750/8270             | 900 / 130               | 23.8 / 30.0                  | 6959613729188   |
| 11R24.5     | 16 / H  | 149/146 L                    | 8.25            | 1104 / 43.5                    | 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 23.8 / 30.0                  | 6959613724565   |

| SIZE    | PR / LR | LOAD INDEX /<br>SPEED SYMBOL |      | OVERALL<br>DIAMETER<br>[MM / IN ] | SECTION<br>WIDTH<br>[MM / IN] | SINGLE<br>LOAD<br>[KG/LBS] | DUAL LOAD<br>[KG/LBS] | PRESSURE<br>[KPA / PSI] | TREAD<br>DEPTH<br>[MM/32NDS] | PRODUCT<br>CODE |
|---------|---------|------------------------------|------|-----------------------------------|-------------------------------|----------------------------|-----------------------|-------------------------|------------------------------|-----------------|
| 11R22.5 | 16 / H  | 146/143 L                    | 8.25 | 1065 / 41.9                       | 279 / 11.0                    | 3000/6610                  | 2725/6005             | 830 / 120               | 26.2 / 33.0                  | 6959613724572   |
| 11R24.5 | 16 / H  | 149/146 L                    | 8.25 | 1104 / 43.5                       | 279 / 11.0                    | 3250/7160                  | 3000/6610             | 830 / 120               | 26.2 / 33.0                  | 6959613724589   |

COMMERCIAL TRUCK

## **Extended Service Life**

Premium severe service compound offers outstanding cut/chip resistance and extended service life in tough driving conditions.

## **Ultimate Off-Road Traction**

Extra deep 33/32nd aggressive self-cleaning tread helps resist mud or snow buildup and promote ultimate traction.

## **Enhanced Stability**

Optimized block design with stability bridges allows for greater stability and constant grip.

## **Guaranteed Retreadability**

Premium enhanced casing construction with deep undertread provides excellent retreadability.



3401 Mallory Lane, ste 200 | Franklin, TN 37067 | 615.535.1358 | customerservice@ketertireusa.com

KeterTireUSA.com

DRIVE THE NEW WORLD!