



Long Service Life

Innovative tread compound with advanced tread design delivers wear resistance and scrubbing resistance for long service life.

Superior Traction

Open shoulder design delivers enhanced traction and acceleration in all weather conditions.

Enhanced Handling

Aggressive design with wide footprint delivers enhanced handling and superior brake response.

Guaranteed Retreadability

Premium casing construction provides toughness and durability for guaranteed retreadability.

SIZE	PR / LR	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER [MM / IN]	SECTION WIDTH [MM / IN]	SINGLE LOAD [KG/LBS]	DUAL LOAD [KG/LBS]	PRESSURE [KPA / PSI]	TREAD DEPTH [MM / 32NDS]	PRODUCT CODE
225/70R19.5	14 / G	128/126 L	6.75	811 / 31.9	226 / 8.9	1800 / 3970	1700 / 3750	760 / 110	15.0 / 19.0	6959613702686
245/70R19.5	16 / H	135/133 L	7.50	839 / 33.0	248 / 9.8	2180 / 4805	2060 / 4540	830 / 120	15.9 / 20.0	6959613702693
10R22.5	14 / G	141/139 M	7.50	1020 / 40.2	254 / 10.0	2575 / 5675	2430 / 5355	790 / 115	18.3 / 23.0	6959613724169
11R22.5	14 / G	144/142 L	8.25	1065 / 41.9	279 / 11.0	2800 / 6175	2650 / 5840	720 / 105	20.6 / 26.0	6959613724176
11R22.5	16 / H	146/143 L	8.25	1065 / 41.9	279 / 11.0	3000 / 6610	2725 / 6005	830 / 120	20.6 / 26.0	6959613724183
255/70R22.5	16 / H	140/137 L	7.50	930 / 36.6	255 / 10.0	2500 / 5510	2300 / 5070	830 / 120	17.5 / 22.0	6959613724213
295/75R22.5	14 / G	144/141 L	8.25	1020 / 40.2	298 / 11.7	2800 / 6175	2575 / 5675	760 / 110	20.6 / 26.0	6959613724220
295/75R22.5	16 / H	146/143 L	8.25	1020 / 40.2	298 / 11.7	3000 / 6610	2725 / 6005	830 / 120	20.6 / 26.0	6959613729201
11R24.5	14 / G	146/143 L	8.25	1116 / 43.9	279 / 11.0	3000 / 6610	2725 / 6005	720 / 105	20.6 / 26.0	6959613724190
11R24.5	16 / H	149/146 L	8.25	1116 / 43.9	279 / 11.0	3250 / 7160	3000 / 6610	830 / 120	20.6 / 26.0	6959613724206
285/75R24.5	14 / G	144/141 L	8.25	1056 / 41.6	283 / 11.1	2800 / 6175	2575 / 5675	760 / 110	22.5 / 28.3	6959613729225
285/75R24.5	16 / H	147/144 L	8.25	1050 / 41.3	283 / 11.1	3075 / 6780	2800 / 6175	830 / 120	22.5 / 28.3	6959613729232