



Long Service Life

Premium chip/cut resistant compound offers long service life in on an doff road applications.

Improved Stability

Optimized tread design with wider footprint improves stability and traction on various driving surfaces.

Adaptable Flexibility

Special bead bundle package allows more flexibility in dealing with road obstacles.

Guaranteed Retreadability

Premium enhanced casing construction offers toughness and outstanding performance through retread cycle.

SIZE	PR / LR	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER [MM / IN]	SECTION WIDTH [MM / IN]	SINGLE LOAD [KG/LBS]	DUAL LOAD [KG/LBS]	PRESSURE [KPA / PSI]	TREAD DEPTH [MM / 32NDS]	PRODUCT CODE
11R22.5	16 / H	148/145 L	8.25	1065 / 41.9	279 / 11.0	3150 / 6940	2900 / 6390	850 / 123	18.3 / 23.0	6959613724480
11R22.5	14 / G	144/142 L	8.25	1065 / 41.9	279 / 11.0	2800 / 6175	2650 / 5840	720 / 105	18.3 / 23.0	6959613702761
12R22.5	18 / J	152/149 K	9.00	1085 / 42.7	300 / 11.8	3550 / 7830	3250 / 7165	830 / 120	18.3 / 23.0	6959613724510
255/70R22.5	16 / H	140/137 L	7.50	930 / 36.6	255 / 10.0	2500 / 5510	2300 / 5070	830 / 120	15.9 / 20.0	6959613702730
275/70R22.5	16 / H	148/145 M	8.25	958 / 37.7	276 / 10.9	3150 / 6940	2900 / 6390	900 / 130	17.5 / 22.0	6959613702747
315/80R22.5	20 / L	161/154 K	9.00	1076 / 42.4	312 / 12.3	4625 / 10200	3750 / 8270	900 / 130	18.3 / 23.0	6959613724503
11R24.5	16 / H	149/146 L	8.25	1104 / 43.5	279 / 11.0	3250 / 7160	3000 / 6610	830 / 120	18.3 / 23.0	6959613724497
11R24.5	14 / G	146/143 L	8.25	1116 / 43.9	279 / 11.0	3000 / 6610	2725 / 6010	720 / 105	18.3 / 23.0	6959613702778