



Extended Service Life

Dependable cut/chip resistance compound promotes extended service life.

Excellent Traction

Rugged lug design with deep non skid offers excellent traction in severe off-highway service.

Guaranteed Retreadability

Premium enhanced casing construction with deep undertread provides excellent retreadability.

SIZE	PR / LR	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER [MM / IN]	SECTION WIDTH [MM / IN]	SINGLE LOAD [KG/LBS]	DUAL LOAD [KG/LBS]	PRESSURE [KPA / PSI]	TREAD DEPTH [MM / 32NDS]	PRODUCT CODE
11R22.5	16 / H	146/143 L	8.25	1065 / 41.9	279 / 11.0	3000 / 6610	2725 / 6005	830 / 120	23.8 / 30.0	6959613724558
11R22.5	14 / G	144/142 L	8.25	1065 / 41.9	279 / 11.0	2800 / 6175	2650 / 5840	720 / 105	23.8 / 30.0	6959613702785
315/80R22.5	20 / L	161/154 K	9.00	1076 / 42.4	312 / 12.3	4625 / 10200	3750 / 8270	900 / 130	23.8 / 30.0	6959613729188
11R24.5	16 / H	149/146 L	8.25	1104 / 43.5	279 / 11.0	3250 / 7160	3000 / 6610	830 / 120	23.8 / 30.0	6959613724565
11R24.5	14 / G	146/143 L	8.25	1116 / 43.9	279 / 11.0	3000 / 6610	2725 / 6010	720 / 105	23.8 / 30.0	6959613702792