



Low Rolling Resistance

Special tread compound with shallow non-skid offers low rolling resistance.

Enhanced Toughness and Even Wear

Solid shoulder rib with unique pressure distribution grooves delivers enhanced toughness and promotes long, even wear.

Wet Weather Stability

Wide center groove delivers superior water evacuation for increased stability in wet road conditions.

Guaranteed Retreadability

Premium casing construction promotes multiple retreads.

SIZE	PR / LR	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER [MM / IN]	SECTION WIDTH [MM / IN]	SINGLE LOAD [KG/LBS]	DUAL LOAD [KG/LBS]	PRESSURE [KPA / PSI]	TREAD DEPTH [MM / 32NDS]	PRODUCT CODE
11R22.5	14 / G	144/142 M	8.25	1054 / 41.5	279 / 11.0	2800 / 6175	2650 / 5840	720 / 105	11.7 / 14.7	6959613724381
11R22.5	16 / H	146/143 M	8.25	1054 / 41.5	279 / 11.0	3000 / 6610	2725 / 6010	830 / 120	11.7 / 14.7	6959613724398
295/75R22.5	14 / G	144/141 M	8.25	1014 / 39.9	298 / 11.7	2800 / 6175	2575 / 5675	760 / 110	11.7 / 14.7	6959613724435
295/75R22.5	16 / H	146/143 M	8.25	1014 / 39.9	298 / 11.7	3000 / 6610	2725 / 6005	830 / 120	11.7 / 14.7	6959613724442
11R24.5	14 / G	146/143 L	8.25	1116 / 43.9	279 / 11.0	3000 / 6610	2725 / 6010	720 / 105	11.7 / 14.7	6959613724404
11R24.5	16 / H	149/146 L	8.25	1116 / 43.9	279 / 11.0	3250 / 7160	3000 / 6610	830 / 120	11.7 / 14.7	6959613724411