



Long Service Life

Premium chip/cut resistant compound offers long service life in on an doff road applications.

Improved Stability

Optimized tread design with wider footprint improves stability and traction on various driving surfaces.

Adaptable Flexibility

Special bead bundle package allows more flexibility in dealing with road obstacles.

Guaranteed Retreadability

Premium enhanced casing construction offers toughness and outstanding performance through retread cycle.

| SIZE | PR / LR | LOAD INDEX / SPEED SYMBOL | STANDARD RIM | OVERALL DIAMETER [MM / IN] | SECTION WIDTH [MM / IN] | SINGLE LOAD [KG/LBS] | DUAL LOAD [KG/LBS] | PRESSURE [KPA / PSI] | TREAD DEPTH [MM / 32NDS] | PRODUCT CODE |
|-------------|---------|---------------------------|--------------|----------------------------|-------------------------|----------------------|--------------------|----------------------|--------------------------|---------------|
| 11R22.5 | 14 / G | 144/142 L | 8.25 | 1065 / 41.9 | 279 / 11.0 | 2800 / 6175 | 2650 / 5840 | 720 / 105 | 18.3 / 23.0 | 6959613702761 |
| 11R22.5 | 16 / H | 146/143 L | 8.25 | 1065 / 41.9 | 279 / 11.0 | 3000 / 6610 | 2725 / 6010 | 850 / 123 | 18.3 / 23.0 | 6959613724480 |
| 255/70R22.5 | 16 / H | 140/137 L | 7.50 | 930 / 36.6 | 255 / 10.0 | 2500 / 5510 | 2300 / 5070 | 830 / 120 | 15.9 / 20.0 | 6959613702730 |
| 275/70R22.5 | 16 / H | 148/145 M | 8.25 | 958 / 37.7 | 276 / 10.9 | 3150 / 6940 | 2900 / 6390 | 900 / 130 | 17.5 / 22.0 | 6959613702747 |
| 315/80R22.5 | 20 / L | 161/154 K | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4625 / 10200 | 3750 / 8270 | 900 / 130 | 18.3 / 23.0 | 6959613724503 |
| 11R24.5 | 14 / G | 146/143 L | 8.25 | 1116 / 43.9 | 279 / 11.0 | 3000 / 6610 | 2725 / 6010 | 720 / 105 | 18.3 / 23.0 | 6959613702778 |
| 11R24.5 | 16 / H | 149/146 L | 8.25 | 1104 / 43.5 | 279 / 11.0 | 3250 / 7160 | 3000 / 6610 | 830 / 120 | 18.3 / 23.0 | 6959613724497 |