



**NEOTERRA**  
Drive The New World

TRUCK TIRE  
LOAD AND  
INFLATION  
TABLES

**2023**  
**VERSION 1.0**

# Medium Commercial Truck Radials

Radial Ply Tires for Trucks, Buses & Trailers Used in Normal Highway Service

## TIRES MOUNTED ON 15° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (kg./lb.) at various Cold Inflation Pressures(Pressure Listed is the Minimum for the Load)												
		kPa	480	520	550	590	620	660	690	720	760	790	830	850
		psi	70	75	80	85	90	95	100	105	110	115	120	123
215/75R17.5	DUAL	kg	1030	1060	1090	1120	1190	1255	1320	1380	1460	1530	<b>1600 (H)</b> <sup>124</sup>	
		lbs	2275	2340	2405	2470	2625	2770	2915	3045	3220	3375	<b>3530 (H)</b>	
	SINGLE	kg	1180	1210	1240	1270	1340	1405	1470	1530	1610	1680	<b>1750 (H)</b> <sup>127</sup>	
		lbs	2605	2670	2735	2800	2955	3100	3245	3375	3550	3705	<b>3860 (H)</b>	
225/70R19.5	DUAL	kg	1230	1300	1360	1410	1470	1550	1580	1640	<b>1700 (G)</b> <sup>126</sup>			
		lbs	2715	2870	3000	3110	3245	3420	3485	3620	<b>3750 (G)</b>			
	SINGLE	kg	1310	1380	1450	1500	1570	1650	1690	1740	<b>1800 (G)</b> <sup>128</sup>			
		lbs	2890	3045	3200	3310	3465	3640	3730	3840	<b>3970 (G)</b>			
235/75R17.5	DUAL	kg	1920	1990	2050	2100	2160	2240	2270	2330	2410	2460	2530	<b>2575 (J)</b> <sup>141</sup>
		lbs	4235	4390	4520	4630	4765	4940	5005	5140	5315	5425	5580	<b>5680 (J)</b>
	SINGLE	kg	2030	2100	2160	2210	2270	2350	2390	2460	2540	2610	2680	<b>2725 (J)</b> <sup>143</sup>
		lbs	4480	4630	4765	4875	5005	5185	5270	5425	5600	5755	5910	<b>6010 (J)</b>
245/70R19.5	DUAL	kg	1390	1460	1550	1590	1660	1750	1790	1850	1950	1970	<b>2060 (H)</b> <sup>133</sup>	
		lbs	3065	3220	3420	3510	3660	3860	3950	4080	4300	4345	<b>4545 (H)</b>	
	SINGLE	kg	1480	1550	1650	1700	1770	1850	1900	1970	2060	2095	<b>2180 (H)</b> <sup>135</sup>	
		lbs	3265	3420	3640	3750	3905	4080	4190	4345	4545	4620	<b>4810 (H)</b>	
255/70R22.5	DUAL	kg	1630	1710	1800	1860	1940	2000	2020	2090	2120	2230	<b>2300 (H)</b> <sup>137</sup>	
		lbs	3595	3770	3970	4105	4280	4410	4455	4610	4675	4920	<b>5075 (H)</b>	
	SINGLE	kg	1730	1820	1900	1980	2060	2120	2220	2300	2360	2450	<b>2500 (H)</b> <sup>140</sup>	
		lbs	3815	4015	4190	4370	4545	4675	4895	5075	5205	5405	<b>5515 (H)</b>	
285/75R24.5	DUAL	kg	1870	1970	2060	2150	2240	2360	2410	2490	<b>2575 (G)</b> <sup>141</sup>	2660	<b>2800 (H)</b> <sup>144</sup>	
		lbs	4125	4345	4545	4740	4940	5205	5315	5490	<b>5680 (G)</b>	5865	<b>6175 (H)</b>	
	SINGLE	kg	2060	2160	2240	2360	2460	2575	2650	2740	<b>2800 (G)</b> <sup>144</sup>	2920	<b>3075 (H)</b> <sup>147</sup>	
		lbs	4545	4765	4940	5205	5425	5680	5845	6045	<b>6175 (G)</b>	6440	<b>6780 (H)</b>	
295/75R22.5	DUAL	kg	1860	1950	2060	2130	2220	2300	2390	2470	<b>2575 (G)</b> <sup>141</sup>	2630	<b>2725 (H)</b> <sup>143</sup>	
		lbs	4105	4300	4545	4700	4895	5075	5270	5450	<b>5680 (G)</b>	5800	<b>6010 (H)</b>	
	SINGLE	kg	2030	2130	2240	2320	2420	2500	2600	2690	<b>2800 (G)</b> <sup>144</sup>	2870	<b>3000 (H)</b> <sup>146</sup>	
		lbs	4480	4700	4940	5115	5340	5515	5735	5935	<b>6175 (G)</b>	6330	<b>6615 (H)</b>	
11R22.5 Except AP201&MS231	DUAL	kg	1990	2080	2160	2250	2360	2460	2560	<b>2650 (G)</b> <sup>142</sup>	2680	2710	<b>2725 (H)</b> <sup>143</sup>	
		lbs	4390	4590	4765	4965	5205	5425	5645	<b>5845 (G)</b>	5910	5975	<b>6010 (H)</b>	
	SINGLE	kg	2050	2160	2260	2370	2500	2600	2700	<b>2800 (G)</b> <sup>144</sup>	2870	2940	<b>3000 (H)</b> <sup>146</sup>	
		lbs	4520	4765	4985	5225	5515	5735	5955	<b>6175 (G)</b>	6330	6485	<b>6615 (H)</b>	
11R22.5 AP201&MS231	DUAL	kg	1990	2080	2160	2250	2360	2460	2560	<b>2650 (G)</b> <sup>142</sup>	2680	2710	2725	<b>2900 (H)</b> <sup>145</sup>
		lbs	4390	4590	4765	4965	5205	5425	5645	<b>5845 (G)</b>	5910	5975	6010	<b>6395 (H)</b>
	SINGLE	kg	2050	2160	2260	2370	2500	2600	2700	<b>2800 (G)</b> <sup>144</sup>	2870	2940	3000	<b>3150 (H)</b> <sup>148</sup>
		lbs	4520	4765	4985	5225	5515	5735	5955	<b>6175 (G)</b>	6330	6485	6615	<b>6945 (H)</b>
11R24.5	DUAL	kg	2110	2210	2300	2390	2500	2580	2660	<b>2725 (G)</b> <sup>143</sup>	2820	2910	<b>3000 (H)</b> <sup>146</sup>	
		lbs	4655	4875	5075	5270	5515	5690	5865	<b>6010 (G)</b>	6220	6420	<b>6615 (H)</b> <sup>149</sup>	
	SINGLE	kg	2190	2300	2410	2520	2650	2770	2890	<b>3000 (G)</b> <sup>146</sup>	3080	3160	<b>3250 (H)</b>	
		lbs	4830	5075	5315	5560	5845	6110	6375	<b>6615 (G)</b>	6795	6970	<b>7165 (H)</b>	

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

Light Truck Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

## TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures											
		kPa psi	250 35	280 40	300 45	350 50	380 55	400 60	450 65	480 70	500 75	550 80	650 95
LT215/85R16	DUAL	kg	630	675	720	800	835	870	975	1000	1030	<b>1120 (E)</b> <sup>112</sup>	
		lbs	1390	1490	1590	1765	1845	1920	2150	2205	2275	<b>2470 (E)</b>	
	SINGLE	kg	695	740	790	880	920	965	1060	1100	1130	<b>1215 (E)</b> <sup>115</sup>	
		lbs	1535	1635	1745	1945	2030	2130	2340	2430	2495	<b>2680 (E)</b>	
LT225/75R16	DUAL	kg	635	680	725	800	845	885	975	1010	1040	<b>1120 (E)</b> <sup>112</sup>	
		lbs	1400	1500	1600	1765	1865	1955	2150	2230	2295	<b>2470 (E)</b>	
	SINGLE	kg	700	745	795	880	930	970	1060	1100	1140	<b>1215 (E)</b> <sup>115</sup>	
		lbs	1545	1645	1755	1945	2055	2140	2340	2430	2515	<b>2680 (E)</b>	
LT235/85R16	DUAL	kg	720	770	820	910	960	1000	1080	1140	1170	<b>1250 (E)</b> <sup>116</sup>	
		lbs	1590	1700	1810	2010	2120	2205	2385	2515	2580	<b>2760 (E)</b>	
	SINGLE	kg	790	850	900	1000	1060	1100	1190	1250	1290	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1745	1875	1985	2205	2340	2430	2625	2760	2845	<b>3090 (E)</b>	
LT245/75R16	DUAL	kg	720	770	820	910	960	1000	1080	1140	1170	<b>1250 (E)</b> <sup>116</sup>	
		lbs	1590	1700	1810	2010	2120	2205	2385	2515	2580	<b>2760 (E)</b>	
	SINGLE	kg	790	850	900	1000	1060	1100	1190	1250	1290	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1745	1875	1985	2205	2340	2430	2625	2760	2845	<b>3090 (E)</b>	
LT255/70R16	DUAL	kg	730	780	830	900	970	1010	1120	1150	1180	<b>1285 (E)</b> <sup>117</sup>	
		lbs	1610	1720	1830	1985	2140	2230	2470	2540	2605	<b>2835 (E)</b>	
	SINGLE	kg	800	855	910	1000	1065	1110	1215	1265	1300	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1765	1885	2010	2205	2350	2450	2680	2790	2870	<b>3090 (E)</b>	
LT265/70R16	DUAL	kg	770	825	875	975	1030	1070	1180	1220	1250	<b>1320 (E)</b> <sup>118</sup>	
		lbs	1700	1820	1930	2150	2275	2360	2605	2690	2760	<b>2915 (E)</b>	
	SINGLE	kg	845	905	960	1060	1130	1180	1285	1340	1370	<b>1450 (E)</b> <sup>121</sup>	
		lbs	1865	2000	2120	2340	2495	2605	2835	2955	3025	<b>3200 (E)</b>	
LT265/70R17	DUAL	kg	800	855	910	1030	1070	1110	1215	1240	1260	<b>1320 (E)</b> <sup>118</sup>	
		lbs	1765	1885	2010	2275	2360	2450	2680	2735	2780	<b>2915 (E)</b>	
	SINGLE	kg	880	940	1000	1120	1170	1220	1320	1360	1390	<b>1450 (E)</b> <sup>121</sup>	
		lbs	1945	2075	2205	2470	2580	2690	2915	3000	3065	<b>3200 (E)</b>	
LT265/70R18	DUAL	kg	830	890	945	1060	1110	1160	1285	1315	1350	<b>1450 (E)</b> <sup>121</sup>	
		lbs	1830	1965	2085	2340	2450	2560	2835	2900	2980	<b>3200 (E)</b>	
	SINGLE	kg	910	975	1040	1150	1220	1270	1400	1440	1480	<b>1600 (E)</b> <sup>124</sup>	
		lbs	2010	2150	2295	2540	2690	2800	3090	3175	3265	<b>3530 (E)</b>	
LT265/75R16	DUAL	kg	810	865	920	1030	1080	1130	1250	1280	1310	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1790	1910	2030	2275	2385	2495	2760	2825	2890	<b>3090 (E)</b>	
	SINGLE	kg	890	950	1010	1120	1180	1240	1360	1400	1440	<b>1550 (E)</b> <sup>123</sup>	
		lbs	1965	2095	2230	2470	2605	2735	3000	3090	3175	<b>3420 (E)</b>	
LT275/55R20	DUAL	kg	750	790	840	925	980	1030	1120	1160	1200	<b>1285 (E)</b> <sup>117</sup>	
		lbs	1655	1745	1855	2040	2165	2275	2470	2560	2650	<b>2835 (E)</b>	
	SINGLE	kg	825	875	925	1030	1080	1130	1215	1280	1320	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1820	1930	2040	2275	2385	2495	2680	2825	2915	<b>3090 (E)</b>	
LT275/65R18	DUAL	kg	820	875	930	1060	1100	1140	1250	1290	1330	<b>1400 (E)</b> <sup>120</sup>	
		lbs	1810	1930	2055	2340	2430	2515	2760	2845	2935	<b>3090 (E)</b>	
	SINGLE	kg	900	960	1020	1150	1200	1250	1360	1410	1460	<b>1550 (E)</b> <sup>123</sup>	
		lbs	1985	2120	2250	2540	2650	2760	3000	3110	3220	<b>3420 (E)</b>	
LT275/65R20	DUAL	kg	880	940	1000	1120	1170	1220	1320	1380	1430	<b>1550 (E)</b> <sup>123</sup>	
		lbs	1945	2075	2205	2470	2580	2690	2915	3045	3155	<b>3420 (E)</b>	
	SINGLE	kg	965	1035	1100	1215	1290	1340	1450	1510	1570	<b>1700 (E)</b> <sup>126</sup>	
		lbs	2130	2285	2430	2680	2845	2955	3200	3330	3465	<b>3750 (E)</b>	
LT275/70R18	DUAL	kg	875	930	990	1120	1180	1220	1320	1370	1420	<b>1500 (E)</b> <sup>122</sup>	
		lbs	1930	2055	2185	2470	2605	2690	2915	3025	3135	<b>3310 (E)</b>	
	SINGLE	kg	960	1030	1090	1215	1290	1340	1450	1510	1560	<b>1650 (E)</b> <sup>125</sup>	
		lbs	2120	2275	2405	2680	2845	2955	3200	3330	3440	<b>3640 (E)</b>	

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

Light Truck Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service

## TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE DESIGNATION	USAGE	Tire Load Limits (lb.) at various Cold Inflation Pressures											
		kPa	250	280	300	350	380	400	450	480	500	550	650
		psi	35	40	45	50	55	60	65	70	75	80	95
LT285/55R20	DUAL	kg	785	835	885	1000	1040	1080	1180	1225	1270	<b>1360 (E)</b> <sup>119</sup>	
		lbs	1735	1845	1955	2205	2295	2385	2605	2705	2800	<b>3000 (E)</b>	
	SINGLE	kg	860	920	975	1090	1140	1190	1285	1350	1400	<b>1500 (E)</b> <sup>122</sup>	
		lbs	1900	2030	2150	2405	2515	2625	2835	2980	3090	<b>3310 (E)</b>	
LT285/60R20	DUAL	kg	865	915	975	1060	1125	1190	1285	1340	1390	<b>1500 (E)</b> <sup>122</sup>	
		lbs	1910	2020	2150	2340	2485	2625	2835	2955	3065	<b>3310 (E)</b>	
	SINGLE	kg	950	1010	1070	1180	1240	1310	1400	1470	1530	<b>1650 (E)</b> <sup>125</sup>	
		lbs	2095	2230	2360	2605	2735	2890	3090	3245	3375	<b>3640 (E)</b>	
LT285/65R18	DUAL	kg	860	930	975	1060	1135	1190	1320	1360	1400	<b>1500 (E)</b> <sup>122</sup>	
		lbs	1900	2055	2150	2340	2505	2625	2915	3000	3090	<b>3310 (E)</b>	
	SINGLE	kg	945	1010	1070	1180	1240	1310	1450	1490	1540	<b>1650 (E)</b> <sup>125</sup>	
		lbs	2085	2230	2360	2605	2735	2890	3200	3285	3400	<b>3640 (E)</b>	
LT285/65R20	DUAL	kg	920	990	1050	1180	1230	1280	1400	1450	1500	<b>1600 (E)</b> <sup>124</sup>	
		lbs	2030	2185	2315	2605	2715	2825	3090	3200	3310	<b>3530 (E)</b>	
	SINGLE	kg	1010	1080	1150	1285	1350	1410	1550	1600	1650	<b>1750 (E)</b> <sup>127</sup>	
		lbs	2230	2385	2540	2835	2980	3110	3420	3530	3640	<b>3860 (E)</b>	
LT285/70R17	DUAL	kg	890	950	1010	1150	1190	1230	1320	1320	1320	<b>1320 (E)</b> <sup>118</sup>	
		lbs	1965	2095	2230	2540	2625	2715	2915	2915	2915	<b>2915 (E)</b>	
	SINGLE	kg	980	1050	1110	1250	1300	1350	1450	1450	1450	<b>1450 (E)</b> <sup>121</sup>	
		lbs	2165	2315	2450	2760	2870	2980	3200	3200	3200	<b>3200 (E)</b>	
LT285/75R16	DUAL	kg	900	965	1030	1150	1210	1260	1360	1420	1470	<b>1550 (E)</b> <sup>123</sup>	
		lbs	1985	2130	2275	2540	2670	2780	3000	3135	3245	<b>3420 (E)</b>	
	SINGLE	kg	990	1060	1130	1250	1320	1380	1500	1550	1610	<b>1700 (E)</b> <sup>126</sup>	
		lbs	2185	2340	2495	2760	2915	3045	3310	3420	3550	<b>3750 (E)</b>	
LT285/75R18	DUAL	kg	965	1040	1100	1250	1300	1350	1450	1510	1570	<b>1700 (E)</b> <sup>126</sup>	
		lbs	2130	2295	2430	2760	2870	2980	3200	3330	3465	<b>3750 (E)</b>	
	SINGLE	kg	1060	1140	1210	1360	1420	1480	1600	1670	1730	<b>1850 (E)</b> <sup>129</sup>	
		lbs	2340	2515	2670	3000	3135	3265	3530	3685	3815	<b>4080 (E)</b>	
LT305/55R20	DUAL	kg	875	930	985	1120	1160	1200	1320	1360	1400	<b>1500 (F)</b> <sup>122</sup>	
		lbs	1930	2055	2175	2470	2560	2650	2915	3000	3090	<b>3310 (F)</b>	
	SINGLE	kg	950	1020	1080	1215	1270	1320	1450	1495	1540	<b>1650 (F)</b> <sup>125</sup>	
		lbs	2095	2250	2385	2680	2800	2915	3200	3300	3400	<b>3640 (F)</b>	
LT305/70R16	DUAL	kg	925	1010	1080	1215	1270	1320	<b>1450 (E)</b> <sup>121</sup>	1500	1550	<b>1650 (F)</b> <sup>125</sup>	
		lbs	2040	2230	2385	2680	2800	2915	<b>3200 (E)</b>	3310	3420	<b>3640 (F)</b>	
	SINGLE	kg	1030	1110	1190	1320	1390	1450	<b>1600 (E)</b> <sup>124</sup>	1650	1700	<b>1800 (F)</b> <sup>128</sup>	
		lbs	2275	2450	2625	2915	3065	3200	<b>3530 (E)</b>	3640	3750	<b>3970 (F)</b>	
LT315/70R17	DUAL	kg	1060	1110	1170	1320	1320	1320	<b>1320 (E)</b> <sup>118</sup>	1320	1320	<b>1320 (F)</b> <sup>118</sup>	
		lbs	2340	2450	2580	2915	2915	2915	<b>2915 (E)</b>	2915	2915	<b>2915 (F)</b>	
	SINGLE	kg	1150	1220	1290	1450	1450	1450	<b>1450 (E)</b> <sup>121</sup>	1450	1450	<b>1450 (F)</b> <sup>121</sup>	
		lbs	2540	2690	2845	3200	3200	3200	<b>3200 (E)</b>	3200	3200	<b>3200 (F)</b>	
LT325/60R20	DUAL	kg	1060	1100	1170	1320	1380	1440	<b>1550 (E)</b> <sup>123</sup>	1550	1550	<b>1550 (F)</b> <sup>123</sup>	
		lbs	2340	2430	2580	2915	3045	3175	<b>3420 (E)</b>	3420	3420	<b>3420 (F)</b>	
	SINGLE	kg	1150	1220	1290	1450	1520	1580	<b>1700 (E)</b> <sup>126</sup>	1700	1700	<b>1700 (F)</b> <sup>126</sup>	
		lbs	2540	2690	2845	3200	3355	3485	<b>3750 (E)</b>	3750	3750	<b>3750 (F)</b>	

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.

# Commercial Light Truck Radials

*Light Truck Radial Ply Tires for Trucks, Buses, Trailers & Multipurpose Passenger Vehicles Used in Normal Highway Service*

## TIRES MOUNTED ON 5° DROP CENTER RIMS

TIRE SIZE	Tire Load Limits (lb.) at various Cold Inflation Pressures											
	kPa	250	280	300	350	380	400	450	480	500	550	650
DESIGNATION	psi	35	40	45	50	55	60	65	70	75	80	95
31X10.50R15LT	kg	800	880	955	<b>1030 (C)</b>							
	lbs	1765	1945	2110	<b>2275 (C)</b> <sup>109</sup>							
33X12.50R17LT	kg	925	1025	1105	1180	1260	1330	<b>1400 (E)</b>	1415	1435	<b>1450 (F)</b>	
	lbs	2040	2260	2440	2605	2780	2935	<b>3090 (E)</b> <sup>120</sup>	3120	3165	<b>3200 (F)</b> <sup>120</sup>	
33X12.50R18LT	kg	900	975	1055	1120	1200	1270	<b>1320 (E)</b>	1400	1465	<b>1500 (F)</b>	
	lbs	1985	2150	2330	2470	2650	2800	<b>2915 (E)</b> <sup>118</sup>	3090	3230	<b>3310 (F)</b> <sup>122</sup>	
33x12.50R20LT	kg	800	870	940	1000	1135	1135	<b>1180 (E)</b>	1250	1305	<b>1360 (F)</b>	
	lbs	1765	1920	2075	2205	2505	2505	<b>2605 (E)</b> <sup>114</sup>	2760	2880	<b>3000 (F)</b> <sup>119</sup>	
33x12.50R22LT	kg	690	755	815	875	930	980	<b>1030 (E)</b>	1080	1130	<b>1180 (F)</b>	
	lbs	1525	1665	1800	1930	2055	2165	<b>2275 (E)</b> <sup>109</sup>	2385	2495	<b>2605 (F)</b> <sup>114</sup>	
35x12.50R17LT	kg	1090	1190	1290	1360	1390	1420	<b>1450 (E)</b>	1450	1450	<b>1450 (F)</b>	
	lbs	2405	2625	2845	3000	3065	3135	<b>3200 (E)</b> <sup>121</sup>	3200	3200	<b>3200 (F)</b> <sup>121</sup>	
35x12.50R18LT	kg	1060	1150	1240	1320	1415	1495	<b>1550 (E)</b>	1645	1720	<b>1800 (F)</b>	
	lbs	2340	2540	2735	2915	3120	3300	<b>3420 (E)</b> <sup>123</sup>	3630	3795	<b>3970 (F)</b> <sup>128</sup>	
35x12.50R20LT	kg	950	1050	1130	1215	1290	1365	<b>1450 (E)</b>	1505	1570	<b>1650 (F)</b>	
	lbs	2095	2315	2495	2680	2845	3010	<b>3200 (E)</b> <sup>121</sup>	3320	3465	<b>3640 (F)</b> <sup>125</sup>	
35x12.50R22LT	kg	850	930	1010	1090	1150	1215	<b>1285 (E)</b>	1340	1400	<b>1450 (F)</b>	
	lbs	1875	2055	2230	2405	2540	2680	<b>2835 (E)</b> <sup>117</sup>	2955	3090	<b>3200 (F)</b> <sup>121</sup>	
37x12.50R20LT	kg	1120	1225	1325	1400	1515	1600	<b>1700 (E)</b>	1735	1765	<b>1800 (F)</b>	
	lbs	2470	2705	2925	3090	3340	3530	<b>3750 (E)</b> <sup>126</sup>	3825	3895	<b>3970 (F)</b> <sup>128</sup>	
37x12.50R17LT	kg	1250	1365	1475	<b>1600 (D)</b>							
	lbs	2760	3010	3255	<b>3530 (D)</b> <sup>124</sup>							
37x13.50R20LT	kg	1150	1265	1370	1450	1560	1645	<b>1750 (E)</b>	1765	1785	<b>1800 (F)</b>	
	lbs	2540	2790	3025	3200	3440	3630	<b>3860 (E)</b> <sup>127</sup>	3895	3940	<b>3970 (F)</b> <sup>128</sup>	
37x13.50R24LT	kg	925	1020	1100	1180	1255	1325	<b>1400 (E)</b>	1465	1525	<b>1600 (F)</b>	
	lbs	2040	2250	2430	2605	2770	2925	<b>3090 (E)</b> <sup>120</sup>	3230	3365	<b>3530 (F)</b> <sup>124</sup>	

NOTES: Letters in parentheses denote Load Range for which boldface loads and inflations are maximum.

International Load Index numbers are shown after Load Range.

IMPORTANT — Always use approved tire and rim combinations for diameter and contours.