NEOMAX-MT

Mud Terrain



ROLLING RESISTANCE

WET PERFORMANCE

QUIETNESS

COMFORT

TREAD LIFE



Maximum Traction

Advanced tread compound and aggressive block design ensures maximus traction and grip in severe off -road conditions.



Tough and Durable

Hardworking wraparound tread with enhanced steel belt package construction optimizes sidewall traction and puncture resistance in deep mud, sand and rocks.



Confident Handling

Self-cleaning tread and shoulder area guarantees consistent traction and grip power.



NEOMAX-MT SIZE & SPECIFICATION

SIZE	PLY RATING / LOAD RANGE	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER (mm/in)	SECTION WIDTH (mm/in)	TREAD DEPTH (mm/32nds)
LT245/75R16	10 / E	120/116 / Q	7J	780 / 30.7	248 / 9.8	15.5 / 19.5
LT285/75R16	10 / E	126/123 / Q	8J	840 / 33.1	286 / 11.3	15.5 / 19.5
LT305/70R16	12 / F	128/125 / Q	9J	834 / 32.8	311 / 12.2	15.5 / 19.5
LT285/65R18	10 / E	125/122 / Q	8½J	833 / 32.8	292 / 11.5	15.5 / 19.5
LT305/55R20	12 / F	125/122 / Q	9 ½J	844 / 33.2	316 / 12.4	15.5 / 19.5
LT325/60R20	12 / F	126/123 / Q	9½J	898 / 35.4	331 / 13.0	15.5 / 19.5
31x10.50R15LT	6 / C	109 / Q	8½J	775 / 30.5	268 / 10.6	15.5 / 19.5
33x12.50R15LT	6 / C	108 / Q	10J	826 / 32.5	318 / 12.5	15.5 / 19.5
35x12.50R15LT	6 / C	113 / Q	10J	877 / 34.5	318 / 12.5	15.5 / 19.5
33x12.50R17LT	12 / F	121 / Q	10J	832 / 32.8	318 / 12.5	15.5 / 19.5
35x12.50R17LT	12 / F	121 / Q	10J	883 / 34.8	318 / 12.5	15.5 / 19.5
37x12.50R17LT	8 / D	124 / Q	10J	934 / 36.8	318 / 12.5	15.5 / 19.5
37x13.50R17LT	10 / E	121 / Q	11J	928 / 36.5	345 / 13.6	15.5 / 19.5
33x12.50R18LT	12 / F	122 / Q	10J	832 / 32.8	318 / 12.5	15.5 / 19.5
35x12.50R18LT	12 / F	128 / Q	10J	883 / 34.8	318 / 12.5	15.5 / 19.5
33x12.50R20LT	12 / F	119 / Q	10J	832 / 32.8	318 / 12.5	15.5 / 19.5
35x12.50R20LT	12 / F	125 / Q	10J	883 / 34.8	318 / 12.5	15.5 / 19.5
37x13.50R20LT	12 / F	128 / Q	11J	934 / 36.8	345 / 13.6	15.5 / 19.5
33x12.50R22LT	12 / F	114 / Q	10J	832 / 32.8	318 / 12.5	15.5 / 19.5
35x12.50R22LT	12 / F	121 / Q	10J	883 / 34.8	318 / 12.5	15.5 / 19.5
37x13.50R22LT	12 / F	128 / Q	11J	928 / 36.5	345 / 13.6	15.5 / 19.5
37x13.50R24LT	12 / F	124 / Q	11J	934 / 36.8	345 / 13.6	15.5 / 19.5
• LT265/75R16	10 / E	123/120 / Q	7½J	804 / 31.7	267 / 10.5	-
• 37x9.50R15LT	10 / E	104 / Q	7½J	750 / 29.5	240 / 9.4	-
• 31x10.50R15LT	10 / E	109 / Q	8½J	775 / 30.5	268 / 10.6	-

(• COMING SOON)