

NEOTEC VAN

Light Truck




Super Loading and Wear Resistance

Central 'diamond' tread blocks and semi-closed design of the shoulder can supply super loading ability and improve wear resistance.



Quiet Ride and Wet Grip

The Longitudinal and lateral grooves can reduce noise while improving wet grip.



Prevents Irregular Wear

Patented contour design for light trucks can prevent irregular wear.

SIZE	PLY RATING / LOAD RANGE	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	OVERALL DIAMETER (mm/in)	SECTION WIDTH (mm/in)	TREAD DEPTH (mm/32nds)
195/R14C	8 / D	102/100 / S	5½J	666 / 26.2	198 / 7.8	9 / 11.3
195/15C	8 / D	106/104 / S	5½J	690 / 27.2	198 / 7.8	9 / 11.3
225/70R15C	10 / E	112/110 / S	6½J	697 / 27.4	228 / 9.0	9 / 11.3
• 215/70R15C	8 / D	109/107 / R	6½J	683 / 26.9	221 / 8.7	-
• 195/75R16C	8 / D	107/105 / R	5½J	698 / 27.5	196 / 7.7	-
• 205/65R16C	8 / D	107/105 / S	6J	672 / 26.5	209 / 8.2	-
• 215/65R16C	8 / D	109/107 / T	6½J	686 / 27.0	221 / 8.7	-
• 225/65R16C	8 / D	112/110 / T	6½J	698 / 27.5	228 / 9.2	-
• 235/65R16C	8 / D	121/119 / T	7J	712 / 28.0	240 / 9.4	-
• 205/70R15C	8 / D	106/104 / T	6J	669 / 26.3	209 / 8.2	-
• 215/70R16C	8 / D	108/106 / T	6½J	708 / 27.9	221 / 8.7	-

(• COMING SOON)